

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

BONAFIDE (AEROSOL)
DA6401

MANUFACTURED FOR:

Drummond American Corporation
600 Corporate Woods Pkwy.
Vernon Hills, Illinois 60061

IN CASE OF EMERGENCY CALL:
ROCKY MOUNTAIN POISON & DRUG CENTER
COLLECT AT: (303) 623-5716

DATE OF PREPARATION:
10/01/93

INFORMATION TELEPHONE NUMBER:
(708) 913-9313

SECTION I - IDENTITY

PRODUCT NUMBER DA6401
PRODUCT NAME BONAFIDE (AEROSOL)
PRODUCT CLASS SOLVENTS

SECTION II - INGREDIENTS

INGREDIENT	CAS NUMBER	%	ACGIH TLV PPM	MG/M ³	PEL PPM	STEL PPM
TRICHLOROETHYLENE *	79-01-6	>95	50	269.0	50.00	200.00
CARBON DIOXIDE	124-38-9	<5	5000	18000	10000.0	30000

* THIS CHEMICAL IS
SUBJECT TO S.A.R.A. TITLE III
SECTION 313 REPORTING

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (degrees F): N/A
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Faster than ether.
PERCENT VOLATILE (By Weight): 100.00 WEIGHT PER GALLON (LBS): 12.14
OPTIONAL INFORMATION:
Appearance and Odor: Narrow cone or stream, no residue on drying.
Chlorinated solvent odor. Specific Gravity: 1.456.
Soluble in water: negligible.

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

BONAFIDE (AEROSOL)
DA6401

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION:
OSHA CLASS N/A U.N. CLASSIFICATION:
DOT CLASS N/A PER DOT N/A
FLASH POINT (Degrees F): N/A PER IMCO N/A
LEL: N/A
UEL: N/A

METHOD: N/A

AEROSOL PRODUCT: Treat as cylinder of compressed gas.
EXTINGUISHING MEDIA:
FOAM CO2 DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS:
At elevated temperatures (over 130 degrees Fahrenheit) containers
may vent, rupture or burst.

SPECIAL FIREFIGHTING PROCEDURES:
Keep containers cool. Use shielding to protect personnel against
bursting, rupturing or venting containers.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:
Hydrogen chloride, phosgene and additional toxic chemicals may be
formed in small amounts.

CONDITIONS TO AVOID:

Do not store above 120 degrees Fahrenheit. Keep from sparks, pilot
lights or open flame.

INCOMPATIBILITY (MATERIALS TO AVOID):
Oxidizing agents.

D.O.T. EMERGENCY RESPONSE INFORMATION:

NOT APPLICABLE

