

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET

7S966

JF764

For Coatings, Resins and Related Materials

DO NOT puncture or store above 120 F. Protect from freezing. DO NOT puncture or incinerate cans. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.
 CALIFORNIA PROPOSITION 65 STATEMENT:
 These products contain a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION I - PRODUCT AND PREPARATION INFORMATION

ACTORER: RUST-OLEUM CORPORATION
 4thome Parkway
 a Hills, IL 60061

EMERGENCY AND INFORMATION TELEPHONE: (708) 367-7700

PRODUCT CLASS: Aerosol Spray Paint

MANUFACTURERS CODE: 2325, 2326, 2348 UNLEADED#, 2364, 2378 and 2391

TRADE NAME: HARD HAT Stripping Paints

DATE OF PREPARATION: April 26, 1993 (rwb)

#NOTE: There is an older leaded version of 2348 which has a separate MSDS.

SECTION II - HAZARDOUS INGREDIENTS

EXPOSURE LIMITS	VAPOR PRESSURE				
INGREDIENT/CAS No	WT %	ACGIH-TLV	OSHA-PEL	LEL	mm Hg@20C
Xylene/1330-20-7	7%	100ppm	100ppm	1.0%	9.5
Toluene/108-88-3	25%*	100ppm	100ppm	1.2%	22.0
VM&P Naphtha/64742-89-8	3-10%*	300ppm	NE	0.9%	2.0
Propane/74-98-6	10%*	NE	1000ppm	2.3%	40psia
Isobutane/75-28-5	10%*	NE	NE	1.9%	40psia

*Nearest 5%

NE-not established NA-not applicable

SECTION III - PHYSICAL DATA

Boiling range: Below 0 F

Evaporation Rate (Ether=1): Slower

Vapor density: Heavier than air

% Volatile (by volume): NA

Wt/gal: NA

pH: NA

SECTION IV - FIRE AND EXPLOSION HAZARDS

Flammability Classification: Extremely Flammable

Flashpoint: <0 F (ICC)

DOT Classification: Consumer Commodity ORM-D

Extinguishing Media: NFPA Class B extinguishers (Carbon dioxide, dry chemical or foam)

Special Fire Fighting Procedures:

Full protective equipment, including self-container breathing apparatus, should be used. Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion. If water is used, fog nozzles are preferred.

Unusual Fire and Explosion Hazards:

Keep away from heat, electrical equipment, sparks, and open flame.

Closed containers may explode when exposed to extreme heat. DO NOT apply to hot surfaces.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

Acute (Inhalation):

Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Repeated overexposures may lead progressively to staggering gait, confusion, unconsciousness or coma. Causes nose and throat irritation.

Acute (Skin or Eye Contact):

Causes eye and skin irritation which may lead to dermatitis with repeated overexposures.

Ingestion:

May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to Xylene and Toluene in lab animals has been associated with liver, kidney, spleen and eye damage as well as anemia. Effects in humans included liver and cardiac abnormalities.

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation:

Remove from exposure, restore breathing, and notify a physician.

Eye Contact:

Flush immediately with large amounts of water for at least 15 minutes.

Notify a physician.

Skin Contact:

Wash affected area with soap and water, remove contaminated clothing, and wash before reuse. Wash hands before eating or smoking.

Ingestion:

DO NOT induce vomiting. Keep person warm, quiet, and get medical attention. Aspiration of this material into the lungs can cause chemical pneumonitis which can be fatal.

SECTION VI - REACTIVITY DATA

Stability: Stable

Incompatible: with strong oxidizing agents

Hazard Decomposition Products: By open flame- Carbon monoxide & Carbon dioxide

Hazardous Polymerization: Will Not Occur

SECTION VII - SPILL OR LEAK PROCEDURES

Release or Spill Procedures:

Remove all sources of ignition, ventilate area and remove with inert absorbent and nonsparking tools

Waste Disposal Method:

Dispose of according to local, state and federal regulations. DO NOT incinerate closed containers.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection:

Use NIOSH approved chemical cartridge respirator (TC23C) to remove solid airborne particles of overspray and organic vapors during spray application.

In confined areas, use NIOSH approved supplied-air respirators or hoods (TC19C).

Eye Protection:

Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment:

Use gloves to prevent contact with skin.

Ventilation:

Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients in SECTION II below acceptable limits.

SECTION IX - SPECIAL PRECAUTIONS AND REGULATORY ISSUES

Shipping and Storage Precautions: