

(009935-0524Z -8C013025-00061430) DATE OF ISSUE 08/07/90 SUPERSEDES 09/01/89

SECTION I - GENERAL INFORMATION

CHEMICAL NAME & SYNONYMS: N/A
 TRADE NAME & SYNONYMS: UGL LATEX TUB & TILE CLK
 CHEMICAL FAMILY: ACRYLIC LATEX SEALANT
 FORMULA: X<--MIXTURE
 MANUFACTURERS NAME: CREED COMPANY DIV. OF PLUMBMASTER INC.
 ADDRESS (NUMBER, STREET, CITY, STATE & ZIP CODE): P.O. BOX 700, CONCORDVILLE, PA 19331
 PREPARED BY: RICHARD STOLLEY/T.S.CHEM. | PRODUCT CODE NUMBER: 00061430 | EMERGENCY TELEPHONE NUMBER: 214 438-1381

SECTION II - HAZARDOUS INGREDIENTS

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS.

CHEMICAL NAME (INGREDIENTS)	HAZARD	TLV	PEL	CAS#
MINERAL SPIRITS	IRRITANT	NA	100PPM	8030-30-6

SECTION III - PHYSICAL DATA

BOILING PT. (FAHRENHEIT)	212 F.	SPEC GRAVITY (H2O=1)	1.61
VAPOR PRESSURE (MM HG)	1.3	COLOR	WHITE
VAPOR DENSITY (AIR=1)	> 1.0	ODOR	ODORLESS

UGL LATEX TUB & TILE CLK

(CONTINUED) SECTION III - PHYSICAL DATA PAGE : 02

PH @ 100%	N/A	CLARITY	OPAQUE
PERCENT VOLATILE BY VOLUME (%)	30.9	EVAPORATION RATE (BU AC = 1)	> 1.0
SOLUBILITY IN WATER	PARTIALLY		
VISCOSITY	PASTE		

SECTION IV - FIRE AND EXPLOSION HAZARD

FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
NON-FLAMM/A	N/A	N/A	N/A
EXTINGUISHING MEDIA	"ALCOHOL"	DRY	WATER
<--FOAM	<--FOAM	<--CO2	X<--SPRAY
		<--CHEMICAL	<--OTHER

SPECIAL FIRE FIGHTING PROCEDURES: WEAR NIOSH/MSHA APPROVED RESPIRATOR WHEN FIGHTING FIRES IN CONFINED AREAS TO PREVENT EXPOSURE TO ACRID SMOKE AND HAZARDOUS DECOMPOSITION PRODUCTS.

UNUSUAL FIRE & EXPLOSION HAZARDS: NONE KNOWN.

NFPA HAZARD RATING (0=INSIGNIFICANT; 1=SLIGHT; 2=MDDERATE; 3=HIGH; 4=EXTREME):
 <--HEALTH <--FLAMMABILITY <--REACTIVITY <--SPECIAL

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

EFFECTS OF OVEREXPOSURE: - ACUTE - (SHORT TERM EXPOSURE)
 EYES: INITIAL IRRITATION.
 INGESTION: MAY CAUSE GENERAL DISCOMFORT AND POSSIBLY NAUSEA.
 - CHRONIC - (LONG TERM EXPOSURE)
 EYES: MAY CAUSE IRRITATION.
 SKIN: MAY CAUSE DEFATTING OF SKIN OR POSSIBLY IRRITATION.
 PRIMARY ROUTE OF ENTRY: <-- INHALATION X<-- INGESTION X<-- ABSORPTION

EMERGENCY & FIRST AID PROCEDURES

INHALATION :
 REMOVE VICTIM TO FRESH AIR AND GIVE OXYGEN IF BREATHING BECOMES DIFFICULT.
 SEE A PHYSICIAN.

EYE CONTACT :
 FLUSH WITH WATER FOR 15 MINUTES AND SEE A PHYSICIAN IF IRRITATION PERSISTS.

SKIN CONTACT :
 WASH AREA WITH SOAP AND WATER. SEE A PHYSICIAN IF IRRITATION DEVELOPS.

INGESTION :
 TAKE TWO GLASSES OF WATER TO DILUTE CONTENTS OF THE STOMACH. DO NOT INDUCE
 VOMITING. SEE A PHYSICIAN IMMEDIATELY.

NOTES TO PHYSICIAN :

N/A

SECTION VI - TOXICITY INFORMATION

PRODUCT CONTAINS CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN BY:

IARC	<--YES	NTP	<--YES	OSHA	<--YES	ACGIH	<--YES	OTHER	<--YES
	X<--NO		X<--NO		X<--NO		X<--NO		X<--NO

MINERAL SPIRITS
 EYE-HMN 880PPM/15M 2
 IHL-HMN TCLD 600MG/M3/8H:IRR 2.

SECTION VII - REACTIVITY DATA

STABILITY	X<--STABLE	<--UNSTABLE	CONDITIONS TO AVOID
			EXCESSIVE TEMPERATURES AND EXCESSIVE FREEZE-THAW CYCLE.

INCOMPATIBILITY (MATERIALS TO AVOID)
 STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS
 ACRYLIC ACID AND OXIDES OF CARBON

HAZARDOUS	WILL NOT OCCUR	MAY OCCUR	CONDITIONS TO AVOID
	X<--	<--	EXCESSIVE TEMPERATURES

UGL LATEX TUB & TILE CLK

SECTION VIII - SPILL OR LEAK PROCEDURES

PAGE : 04

STEPS TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
 APPLY ABSORBANT MATERIAL. SWEEP UP AND DISPOSE OF.

WASTE DISPOSAL METHOD
 DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

NEUTRALIZING AGENT
 N/A

SECTION IX - SPECIAL PROTECTION INFORMATION

REQUIRED VENTILATION
 NORMAL ROOM VENTILATION IS ADEQUATE.

RESPIRATORY PROTECTION
 NOT NORMALLY REQUIRED.

PROTECTIVE GLOVES
 NEOPRENE OR IMPERVIUS

EYE PROTECTION
 SAFETY GLASSES.

OTHER PROTECTION
 EYE WASHERS AND SAFETY SHOWERS

SECTION X - STORAGE AND HANDLING INFORMATION

STORAGE TEMPERATURE	INDOOR	HEATED	REFRIGERATED	OUTDOOR
100 F. <--MAX 40 F. <--MIN	X			

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING
 DO NOT STORE IN AN AREA EXPOSED TO TEMPERATURES
 LESS THAN 40 F.

OTHER PRECAUTIONS
 KEEP OUT OF REACH OF CHILDREN
 KNEED TUBE BEFORE USING IF PRODUCT HAS GONE
 THROUGH FREEZE-THAW CYCLES.

5093049

 CHEMICAL NAME C.A.S. NUMBER UPPER % LIMIT

 N/A

 THOSE INGREDIENTS LISTED ABOVE ARE SUBJECT TO THE REPORTING REQUIREMENTS OF
 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF
 1986 AND 40 CFR PART 372.
 IF UE (USE EXEMPTION) APPEARS UNDER UPPER % LIMIT, END USERS ARE EXEMPT
 FROM NOTIFICATION BECAUSE THE PRODUCT IS USED AND LABELED FOR ROUTINE
 JANITORIAL WORK, OR THE PRODUCT IS USED AND LABELED FOR FACILITY GROUNDS
 MAINTENANCE (SUCH AS FERTILIZERS AND HERBICIDES), OR THE PRODUCT IS USED AND
 LABELED FOR MAINTAINING MOTOR VEHICLES.

 CALIFORNIA PROPOSITION 65
 WARNING: THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) KNOWN TO THE STATE OF
 CALIFORNIA TO CAUSE (1) CANCER OR (2) BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM:
 NONE

SECTION XII - TRANSPORTATION * (FOR FUTURE USE)

 APPLICABLE REGULATIONS
 <--49 CFR <--IMCO <--TARIFF 6 D <--IATA <--MILITARY AIR (AFR 71-4)

 SHIPPING NAME

 HAZARD CLASS | ID NUMBER | REPORT QTY

 LABELS | LIMITED QTY

 UNIT CONTAINER

 DDT SPS CONTAINER | NET EXPLOSIVE WT.

 AEROSOL PROPELLANT(S)

SECTION XIII - REFERENCES

- 1. VENDOR'S MSDS
 2. DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, 6TH EDITION, N. IRVING
 SAX.

 THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED
 ACCURATE IN LIGHT OF CURRENT FORMULATION, HOWEVER, NO WARRANTY
 IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA
 OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CREED COMPANY DIV. OF PLUMBMASTER INC. ASSUMES NO RESPONSIBILITY
 FOR PERSONAL INJURY OR PROPERTY DAMAGE CAUSED BY THE USE, STORAGE
 OR DISPOSAL OF THE PRODUCT IN A MANNER NOT RECOMMENDED ON THE
 PRODUCT LABEL. USERS ASSUME ALL RISKS ASSOCIATED WITH SUCH
 UNRECOMMENDED USE, STORAGE, OR DISPOSAL OF THE PRODUCT.

